
OPTIGRÜN SGL 500

Protection, Separation and Slip Layer

Special fleece to protect the waterproofing with combined separating and sliding function. Suitable as a slip layer under public roof structures thanks to the integrated slip layer in combination with the Optigrün Separation and Slip Layer TGF 0.2.



Material	PP (fleece) and LDPE (coating)
Nominal thickness	approx. 4.0 mm
Grammage	approx. 500 g/m² (total) approx. 300 g/m² (fleece) approx. 200 g/m² (coating)
Colour	white
Tensile	Longitudinal: ≥ 12 kN/m (DIN EN ISO 10319) lateral: ≥ 25 kN/m (DIN EN ISO 10319)
Geotextile robustness class	GRC 5
Friction coefficient with additional PE film	< 0.6 in accordance with the requierements of FLL (DIN 53375)
Delivery weigth	approx. 30.0 kg/roll - approx. 265.0 kg/full euro pallet
Pack size	Diameter approx. 0.30 m, height approx. 2.0 m / per roll
Quantity/ delivered unit	$60 \text{ m}^2/\text{roll} = 2.0 \text{ x} 30.0 \text{ m}$ $480 \text{ m}^2/\text{pallet}$
Delivery form	8 rolls on pallet 800 x 1,200 mm with slight protrusion
Mechanically strengthended	yes
Detector tested	yes
Weather resistance	max. 2 weeks exposure

Area of use

- As a protection and separation layer on waterproofing
- To be used in conjunction with a second film (e.g. 0.2 mm PE film) at the same time as a protection and slip layer under public areas

Specific properties

- 100% PP
- Rotproof, not UV-resistant
- Friction coefficient with additional PE film < 0.6 in accordance with the requirements of FLL (DIN 53375).
- Mechanically strengthened
- Detector tested
- Recyclable

The preceding details are guideline values established under laboratory conditions. These values are subject to a certain manufacturing tolerance. The data contained in this product information sheet represents Optigreen's technical knowledge at the time of publication. Optigreen reserves the right to change and update details in accordance with new insights and to modify specified properties accordingly. No liability accepted for misprints.



Am Birkenstock 15 – 19, 72505 Krauchenwies-Göggingen Tel. +49 7576 772-0, Fax +49 7576 772-299, info@optigruen.de

Optigreen Limited (Service UK only)

Suite G5 Albany Chambers, 26 Bridge Road East Welwyn Garden City (Herts), AL7 1HL

Phone +44 203 5899400, Fax +44 207 1171664, info@optigreen.co.uk