

OPTIGRÜN PLANTER

Plant Containers made from aluminium

Optigreen Aluminium Planter for installation outdoors on roof areas or in earthbound open spaces and for installation indoors. Planter made from aluminium in standard and custom sizes with overflow, insulating cladding, and, where required, with welded junction plates as reinforcement.

On request, available with automated irrigation unit and water level indicator.



Material	Aluminium
Nominal thickness	3 mm
Surface/colour	Coated according to RAL colour fan Special paint on request
Weight	depending on size
Dimensions standard	Rectangular format Length: 400/600/800/1,000/1,200 mm Width: 400/600/800 mm Height: 400/600 mm round Height: 400/500/600/800 mm Ø: 400/500/600/800 mm Custom shapes and sizes available on request
Delivery form	On pallet(s) by forwarding agent
Quantity/ delivered unit	According to size of order
Storage	Individually lying or stacked with insulating strips as an intermediate layer, protect against possible mechanical damage

Area of use

- For installation outdoors on roof areas or in earthbound open spaces
- For installation indoors

Specific properties

- Welded overflow pipe in the base, on request also possible in the side wall
- Side walls and base welded
- Upper container edge folded over inwards twice, visible width from the top 30 mm
- Container walls reinforced with welded junction plates that lie on top of each other
- Lined with polystyrene panels inside as heat/cold protection
- All insulation provided is free of HBCD flame retardant

Weight

The gross weight of the planters must be calculated for the order by Optigreen based on the design.

A distinction is made between:

- Installation outdoors or indoors
- Design with water retention or drip irrigation system



The preceding details are guideline values established under laboratory conditions. These values are subject to a certain manufacturing tolerance. The data contained in this product information sheet represents Optigreen's technical knowledge at the time of publication. Optigreen reserves the right to change and update details in accordance with new insights and to modify specified properties accordingly. No liability accepted for misprints.

Optigrün international AG

Am Birkenstock 15 – 19,
72505 Krauchenwies-Göggingen
Tel. +49 7576 772-0, Fax +49 7576 772-299, info@optigruen.de

Optigreen Limited (Service UK only)

Suite G5 Albany Chambers, 26 Bridge Road East
Welwyn Garden City (Herts), AL7 1HL
Phone +44 203 5899400, Fax +44 207 1171664, info@optigreen.co.uk

