

## **OPTIGRÜN International AG**

Optigrün International AG  
Am Birkenstock 15-19  
G 72505 Krauchenwies-Göggingen

Phone +49 (0)7576 772-0

Fax +49 (0)7576 772-299

[info@optigruen.de](mailto:info@optigruen.de)

[technik@optigruen.de](mailto:technik@optigruen.de)

[www.optigreen.com](http://www.optigreen.com)

....m<sup>2</sup> Optigreen Protection, Separation and Glide Fleece Type SGL 500 and 1 layer  
Optigreen HDPE Slip Sheet with a thickness of 0.2 mm as a slip layer

....m<sup>2</sup> high density insulation per designer's specifications (by others)

....m<sup>2</sup> Optigreen Trickle Protection Mat Type RS as a drainage layer

....m<sup>2</sup> Optigreen Drainage Board Type FKD 25 Plus as a drainage layer capable of  
supporting load from walking; pressure resistance 460 kN/m<sup>2</sup>

....m<sup>2</sup> fill Optigreen Drainage Board Type FKD 25 Plus with stone chippings 2-4 mm

....m<sup>2</sup> Optigreen Filter Fleece Type 300 as filter layer

....m<sup>2</sup> 100 - 300 mm gravel base 0-22 or 0-32 mm used as an equalising layer

....m<sup>2</sup> 30 - 50 mm stone chippings 0-4 mm used as bedding for paving

....m<sup>2</sup> concrete paving at a height of 60 - 120 mm as surface covering (according  
to required load class)